



DUNBAR Heat Shrinkable Tubing Part Number Cross Reference

DUNBAR P/N	AS23053/	Inventory	UL VW-1	TE/Raychem	Sumitomo	3M	Canusa	Alpha
Polyolefin Tubing								
DUNBAR-1605 2:1 Shrink Ratio, Flexible 105°C, 600V Rating UL Rated		No Stock use 1635F Exceeds all Ratings	Yes		C2 A4		CPX51	
DUNBAR-1625 2:1 Shrink Ratio, Flexible 125°C, 600V Rating UL & CSA Rated		No Stock use 1635F Exceeds all Ratings	Yes		F2 F32 F2(Z)	CP-221		FIT-221V
DUNBAR-1635F 2:1 Shrink Ratio, Flexible 135°C, 600V Rating UL, CSA & AS23053/5	/5 Class 1, 2, 3	Spools & 4' Lengths Large Inventory All Colors in Stock	Yes	RNF-100 Versafit	SM12 B2 A2 SM35	FP-301 FP-301VW	CPX100 PO135 CPX876	FIT-221 FIT-221B
DUNBAR-1635F Y/G 2:1 Shrink Ratio, Flexible 135°C, 600V Rating		Spools & 4' Lengths	Yes	DCPT	B2(Y/G)		CPX 201	FIT-260
DUNBAR-1625GT 2:1 Shrink Ratio Very Flexible 125°C, 150V Rating Thin Wall UL & CSA Rated		Spools: Black	Yes	Versafit V4	F4(TW)		none	FIT-221-TW
DUNBAR-1635S 2:1 Shrink Ratio, Semi-Rigid 135°C, 600V Rating AS23053/6* Pending QPL	/6* Class 1 & 2 *Pending QPL	Spools & 4' Lengths Colors available	Yes	CRN	B8 D	SR-350	CHM-140 HM 140	FIT-295
DUNBAR-3635 3:1 Shrink Ratio, Flexible 135°C, 600V Rating, UL, CSA AS23053/5* Pending QPL	/5* Class 4 *Pending QPL	Spools: Most colors stocked All colors available	Yes	RNF-3000	SM23 B2(3X) A2(3X)	SFTW-203	CPX300	FIT-321V
DUNBAR-4635 4:1 Shrink Ratio, Flexible 135°C, 600V Rating UL, CSA		Spools: Black 4' Lengths: Black All colors available	Yes	RP-4800	B2(4X)		none	FIT-421
Specialty Tubing								
DUNBAR-CRFR 2:1 Shrink Ratio 120°C, Rating AS23053/1	/1 Class 1 & 2	Spools: Black	Yes	NT-FR NT	R10	NST	CNP 200	FIT-600
DUNBAR-1675 2:1 Shrink Ratio 175°C, 600V Rating UL & AS23053/8	/8	Spools: Clear/Natural 4' Lengths: Clear/Natural & Black Colors available	Yes	Kynar RW-175	K	Kynar	CKN 175 HA 150	FIT-350
DUNBAR-3675 3:1 Shrink Ratio 175°C, 600V Rating UL		No Stock 8 week lead time	Yes					
DUNBAR-DRET 2:1 Shrink Ratio 120°C, 600V Rating		*Discontinued: Use DR150 DR150 - Higher Temp Rating	Yes	DR-25	R120		CDR 625	none
DUNBAR-DR150 2:1 Shrink Ratio 150°C, 600V Rating AS23053/16	/16	Spools: Black	Yes	DR-25	R120		CDR 625	none
DUNBAR-FK150 2:1 Shrink Ratio 150°C, 600V Rating AS23053/18	/18 Class 2	Spools Only Black & Clear	Yes	RNF-150 (Black) RT-375 (Clear)	none	none	none	none
DUNBAR-V200 2:1 Shrink Ratio 200°C, 600V Rating AS23053/13	/13	Spools Only Black	Yes	Viton	KH230 SM60 SM3-60	VTN-200	Deray VT 220	

Visit us at www.hstesting.com or contact Dunbar for any additional information.

1/1/2021



DUNBAR Heat Shrinkable Tubing Part Number Cross Reference

DUNBAR P/N	AS23053/	Inventory	UL VW-1	TE/Raychem	Sumitomo	3M	Canusa	Alpha
Dual-Wall, Polyolefin Tubing (Melttable Adhesive Inner Wall)								
DUNBAR-2690NW 3:2 Shrink Ratio, Flexible 90°C Rating Semi-Rigid		No Stock 8 week lead time	N/A		O2			
DUNBAR-1625W 2:1 Shrink Ratio, Flexible 125°C, 600V Rating UL, CSA, AS23053/4	/4 Class 2	Spools & 4' Lengths: Black Limited Colors	N/A	TAT-125	O2B2 O2C SM24	EPS-200		FIT-750
DUNBAR-3625WS 3:1 Shrink Ratio, Semi-Rigid 135°C, 600V Rating AS23053/4	/4 Class 1	4' Lengths: Black	N/A	SCL	W5DL	MW		FIT-300
DUNBAR-3635W 3:1 Shrink Ratio, Flexible 135°C, 600V Rating UL, CSA, AS23053/4	/4 Class 3	4' Lengths & Spools (Spools through 1/2") Most colors stocked All colors available	N/A	ATUM 3:1 DWP-125	W3B2 W3F2 W3C	EPS-300	CPA300 CPA100 (CPA100 not UL)	FIT-321
DUNBAR-4635W 4:1 Shrink Ratio, Flexible 135°C, 600V Rating		No Stock 8 week lead time	N/A	ATUM 4:1		EPS-400		none
DUNBAR-4635WS 4:1 Shrink Ratio, Semi-rigid 135°C, 600V Rating		4' Lengths Master Spools for cut to length Standard Spools Black & Clear	N/A	ES-2000 ES-1000	SA2F	SMS TES	Splicemelt	none
DUNBAR-4635WT 4:1 Shrink Ratio, Flexible 135°C Rating, Thin Wall		4' Lengths: Black Spools: Black	N/A	ATUM 4:1	W3B2(4X)	EPS-400		
DUNBAR-4650WS 4:1 Shrink Ratio, Semi-rigid 150°C, 600V Rating Fully Flame Retardant		4' Lengths Master Spools for cut to length Standard Spools Black	N/A	FL 2500 SCT	none		CFRA	none
Medium & Heavy Wall Tubing								
DUNBAR-CATV 3:1 Shrink Ratio, Flexible Adhesive Lined, Medium Wall 125°C/600V		4' Lengths: Black	N/A	TCS SCTV		CCT	CFTV	
DUNBAR-CMWT 3:1 Shrink Ratio, Semi-Rigid Adhesive Lined, Medium Wall 125°C/600V		4' Lengths: Black & Red	N/A	RMW SST BSTS			CFM	FIT-700
DUNBAR-PMWT-FR 3:1 Shrink Ratio, Semi-Rigid AS23053/15 C1 & C2 ABS & DNV	/15 C1 & C2	4' Lengths: Black & Red	N/A	SST-FR BSTS-FR		MDT		
DUNBAR-CHWT 3:1 Shrink Ratio, Semi-Rigid Adhesive Lined, Heavy Wall 125°C/600V		4' Lengths: Black & Red	N/A	RHW SST BSTS			CFW	
DUNBAR-PHWT-FR 3:1 Shrink Ratio, Semi-Rigid AS23053/15 C1 & C2 ABS & DNV	/15 C1 & C2	4' Lengths: Black & Red	N/A	SST-FR BSTS-FR HF		HDT	FCFW	
DUNBAR-BBLV 3:1 Shrink Ratio Adhesive Lined, Medium Wall 125°C / 1kV		No Stock 8 week lead time	N/A					
DUNBAR-BBHV 3:1 Shrink Ratio Adhesive Lined, Medium Wall 125°C / 25kV		No Stock 8 week lead time	N/A					
DUNBAR-BBHT 3:1 Shrink Ratio Adhesive Lined, Medium Wall 125°C / 35kV		No Stock 8 week lead time	N/A					
Non-Shrinkable Polyolefin Tubing								
EIT-600 125°C, 600V UL & CSA Rated		Very Limited Stock 8 week lead time	Yes					