



Quick Selection Chart

Type	Product	Shrink Ratio	Recovery Temp (°C)	Operating Temp (°C)	Voltage (V)	Flame Retardant	Adhesive	UL File No.	MIL-Spec	Available Colors												
										Black	Brown	Red	Orange	Yellow	Green	Blue	Violet	Gray	White	Clear	Pink	
Single Wall Polyolefin	DUNBAR-1635F	2:1	90	-55 ~ 135	600	VW-1 ²	No	E319303	AS23053/5 Class 1, 2 (clear) & 3	Black	Brown	Red	Orange	Yellow	Green	Blue	Violet	Gray	White	Clear	Pink	
	DUNBAR-1635F Y/G	2:1	90	-55 ~ 135	600	VW-1	No	E319303	Commercial													
	DUNBAR-DC-221	2:1	90	-55 ~ 125	600	VW-1 ²	No	E319303	Commercial													
	DUNBAR-DC-M221	2:1	90	-55 ~ 135	600	VW-1 ²	No	E319303	Commercial													
	DUNBAR-1635S	2:1	130	-55 ~ 135	600	VW-1 ²	No	N/A	AS23053/6													
	DUNBAR-3635	3:1	90	-55 ~ 135	600	VW-1 ²	No	E319303	AS23053/5 Class 4													
	DUNBAR-DC-321	3:1	90	-55 ~ 125	600	VW-1 ²	No	N/A	Commercial													
Dual Wall Polyolefin (Adhesive Lined)	DUNBAR-4635	4:1	90	-55 ~ 135	600	VW-1 ²	No	E319303	Commercial													
	DUNBAR-1625W	2:1	120	-55 ~ 125	600	VW-1 ²	Yes	E319314	AS23053/4 Class 2													
	DUNBAR-2690NW	3:2	120	-35 ~ 90	600	No	Yes	N/A	Commercial													
	DUNBAR-2690NW-LT	3:2	80	-35 ~ 90	600	No	Yes	N/A	Commercial													
	DUNBAR-3625WS	3:1	125	-55 ~ 125	600	VW-1 ²	Yes	E319314	AS23053/4 Class 1													
	DUNBAR-3635W	3:1	120	-55 ~ 135	600	VW-1 ²	Yes	E319314	AS23053/4 Class 3													
	DUNBAR-DC-321A	3:1	120	-55 ~ 125	600	VW-1 ²	Yes	E319303	Commercial													
	DUNBAR-DC-M321A	3:1	120	-55 ~ 135	600	VW-1 ²	Yes	E319303	Commercial													
	DUNBAR-4635WS	4:1	130	-55 ~ 130	600	VW-1 ²	Yes	E319314	Commercial													
Medium & Heavy Wall Tubing	DUNBAR-4635WT	4:1	120	-55 ~ 135	600	VW-1 ²	Yes	E319314	Commercial													
	DUNBAR-4650WS	4:1	130	-55 ~ 150	600	VW-1 ²	Yes	E319314	Commercial													
	DUNBAR-CATV	3:1	120	-55 ~ 125	1000	No	Yes	E319303	Commercial													
	DUNBAR-CMWT-FR	3:1	120	-55 ~ 125	1000	VW-1	Yes	E319303	Commercial													
	DUNBAR-CHWT-FR	3:1	120	-55 ~ 125	1000	VW-1	Yes	E319303	Commercial													
DUNBAR-PMWT-FR	3:1	120	-55 ~ 125	1000	VW-1	Yes	E319303	AS23053/15 Class 2														
DUNBAR-PHWT-FR	3:1	120	-55 ~ 125	1000	VW-1	Yes	E319303	AS23053/15 Class 1														

² Exception for Clear Product

Rev. October 2024

Certifications:



ISO 9001:2015
AS9100 Rev D Registered



Underwriters Laboratories Inc.
TUV (R86603)



RoHS



REACH



ABS
Certificate Type of Approval



DNV
Type Approval Certificate



1302 Champion Circle
Carrollton, TX 75006

Tel: (469) 568-0800





Quick Selection Chart

Type	Product	Shrink Ratio	Recovery Temp (°C)	Operating Temp (°C)	Voltage (V)	Flame Retardant	Adhesive	UL File No.	MIL- Spec	Available Colors															
										Black	Brown	Red	Orange	Yellow	Green	Blue	Violet	Gray	White	Clear	Rust				
Specialty Tubing	DUNBAR-FK150	2:1	150	-55 ~ 150	600	VW-1	No	E319303	AS23053/18 Class 2														C		
	DUNBAR-1675	2:1	175	-55 ~ 175	600	VW-1	No	E319303	AS23053/8														C		
	DUNBAR-CRFR	2:1	135	-70 ~ 121	600	VW-1	No	N/A	AS23053/1																
	DUNBAR-DR150	2:1	135	-75 ~ 150	600	VW-1	No	N/A	AS23053/16																
	DUNBAR-V200	2:1	100	-55 ~ 200	600	VW-1	No	N/A	AS23053/13																
	DUNBAR-EV2500	2:1	80	-55 ~ 135	2500	VW-1	No	N/A	Commercial				Orange												
	DUNBAR-BB10kV	2.5:1	120	-40 ~ 125	10000	VW-1	No	N/A	Commercial																Orange
	DUNBAR-BB20kV	2.5:1	120	-40 ~ 125	20000	VW-1	No	N/A	Commercial																Orange
	DUNBAR-BB35kV	2.5:1	120	-40 ~ 125	35000	VW-1	No	N/A	Commercial																Orange
	DUNBAR-WFHS	2:1	80	-40 ~ 125	N/A	N/A	FMVSS 302	No	N/A	Commercial				Orange											
	DUNBAR-DC-EC	2:1	130	-55 ~ 110	N/A	N/A	N/A	Yes	N/A	Commercial															
DUNBAR-FFF	3:1	90	-55 ~ 135	600	600	VW-1	No	E319303	AS23053/5 Class 1		Brown	Red	Orange	Yellow	Green	Blue	Violet	Gray				C	Pink		
Teflon	DUNBAR-FEP1.3	1.3:1	210 ~ 221	-75 ~ 200	2000 ¹	V-0	No	N/A	Commercial															C	
	DUNBAR-FEP1.6	1.6:1	210 ~ 221	-75 ~ 200	2000 ¹	V-0	No	N/A	Commercial															C	
	DUNBAR-PTFE2H	2:1	350	-75 ~ 260	1400 ¹	V-0	No	N/A	Commercial															C	
	DUNBAR-PTFE2S	2:1	350	-75 ~ 260	1400 ¹	V-0	No	N/A	Commercial															C	
	DUNBAR-PTFE2T	2:1	350	-75 ~ 260	1400 ¹	V-0	No	N/A	Commercial															C	
	DUNBAR-PTFE2L	2:1	350	-75 ~ 260	1400 ¹	V-0	No	N/A	Commercial															C	
	DUNBAR-PTFE4	4:1	350	-75 ~ 260	1400 ¹	V-0	No	N/A	Commercial															C	
	DUNBAR-ETFE1.5	1.5:1	175	-75 ~ 150	2000 ¹	V-0	No	N/A	Commercial																C
	DUNBAR-FEP Roll Cover	1.25:1	175	-75 ~ 200	2000 ¹	V-0	No	N/A	Commercial																C
	DUNBAR-PTFE/FEP	Varies	360	-75 ~ 200	2000 ¹	V-0	No	N/A	Commercial																C
	DUNBAR-PTFE0H	0:0	N/A	-75 ~ 260	1400 ¹	V-0	No	N/A	Commercial																C
	DUNBAR-PTFE0S	0:0	N/A	-75 ~ 260	1400 ¹	V-0	No	N/A	M22129																C
	DUNBAR-PTFE0T	0:0	N/A	-75 ~ 260	1400 ¹	V-0	No	N/A	Commercial																C
DUNBAR-PTFE0L	0:0	N/A	-75 ~ 260	1400 ¹	V-0	No	N/A	Commercial																C	

¹ Volts/mil

Rev. October 2024

Certifications:



ISO 9001:2015
AS9100 Rev D Registered



Underwriters Laboratories Inc.
TUV (R86603)



RoHS



REACH



ABS
Certificate Type of Approval



DNV
Type Approval Certificate



1302 Champion Circle
Carrollton, TX 75006

Tel: (469) 568-0800

